

32000PN Pneumatic Oil 32

Document version: Dec 9, 2019



Description

This pneumatic oil 32 is a specific lubricant to lubricate pneumatic tools. The special additives in this oil obtains a good protection against corrosion of ferro an non-ferro metals. This oil has good protection against deposit in the pneumatic system, compatible with seals and gaskets made of synthetic material and excellent micro-fog properties. MPM Pneumatic Oil 32 can be used in air piping systems or micro-fog systems of hammers, pile divers and drilling equipment and pumps.

ISO 6743-11P

| ART. NR. | VOLUME | ITEMS PER UNIT | ITEMS PER PALLET |
|----------|--------|----------------|------------------|
| 32001PN | 1 L | 6 | 450 |
| 32005PN | 5 L | 4 | 112 |
| 32020PN | 20 L | 1 | 30 |
| 32060PN | 60 L | 1 | 12 |
| 32205PN | 205 L | 1 | 2 |
| 32999PN | 1000 L | 1 | - |
| P32000PN | 1 L | 1 | - |



MPM International Oil Company B.V. Cyclotronweg 1 2629 HN Delft Fax number: +31 (0)15 - 251 40 31 info@mpmoil.nl www.mpmoil.nl

Complies to the specifications of

Packaging units

Standard analyses

| TEST | VALUE | |
|------------------------------|-----------|-------|
| Viscosity | ISO VG 32 | |
| Density at 15°C | 0.873 | kg/l |
| Kinematic Viscosity at 40°C | 33.3 | mm2/s |
| Kinematic Viscosity at 100°C | 5.9 | mm2/s |
| Viscosity Index | 122 | |
| Flashpoint COC | 198 | °C |
| Pourpoint | -33 | °C |
| | | |

These characteristics are typical of current production. Variations in these characteristics may occur.

Page 2/2

MPM International Oil Company B.V. Cyclotronweg 1 2629 HN Delft Fax number: +31 (0)15 - 251 40 31 info@mpmoil.nl www.mpmoil.nl