

1

Pneumatic - Spring	3/2	Ordering code 211.11.1	5/2	Pneumatic - Spring			
		<table border="1" style="width: 100%; border-collapse: collapse;"> <tr><td>TYPE</td></tr> <tr><td>32 = 3 ways</td></tr> <tr><td>52 = 5 ways</td></tr> </table>	TYPE	32 = 3 ways	52 = 5 ways		
			TYPE				
32 = 3 ways							
52 = 5 ways							
<p>Weight gr. 3330 Minimum piloting pressure 2,5 bar</p>			<p>Weight gr. 4200 Minimum piloting pressure 2,5 bar</p>				

Operational characteristic						
Fluid	Max working pressure (bar)	Temperature °C	Flow rate at 6 bar with Δp=1 (NI/min)	Orifice size (mm)	Working ports size	Pilot ports size
Filtered and lubricated air	10 bar	-5 - +70	6500 NI/min	mm 20	G 1"	G 1/8"

Pneumatic - Differential external	3/2	Ordering code 211.11.12	5/2	Pneumatic - Differential external			
		<table border="1" style="width: 100%; border-collapse: collapse;"> <tr><td>TYPE</td></tr> <tr><td>32 = 3 ways</td></tr> <tr><td>52 = 5 ways</td></tr> </table>	TYPE	32 = 3 ways	52 = 5 ways		
			TYPE				
32 = 3 ways							
52 = 5 ways							
<p>Weight gr. 3330 Minimum piloting pressure 2,5 bar</p>			<p>Weight gr. 4200 Minimum piloting pressure 2,5 bar</p>				

Operational characteristic						
Fluid	Max working pressure (bar)	Temperature °C	Flow rate at 6 bar with Δp=1 (NI/min)	Orifice size (mm)	Working ports size	Pilot ports size
Filtered and lubricated air	10 bar	-5 - +70	6500 NI/min	mm 20	G 1"	G 1/8"


Pneumatic - Pneumatic	3/2	Ordering code 211.11.11	5/2	Pneumatic - Pneumatic			
		<table border="1" style="width: 100%; border-collapse: collapse;"> <tr><td>TYPE</td></tr> <tr><td>32 = 3 ways</td></tr> <tr><td>52 = 5 ways</td></tr> </table>	TYPE	32 = 3 ways	52 = 5 ways		
			TYPE				
32 = 3 ways							
52 = 5 ways							
<p>Weight gr. 3330 Minimum piloting pressure 2 bar</p>			<p>Weight gr. 4200 Minimum piloting pressure 2 bar</p>				

Operational characteristic						
Fluid	Max working pressure (bar)	Temperature °C	Flow rate at 6 bar with Δp=1 (NI/min)	Orifice size (mm)	Working ports size	Pilot ports size
Filtered and lubricated air	10 bar	-5 - +70	6500 NI/min	mm 20	G 1"	G 1/8"



Pneumatic - Pneumatic

Ordering code
211.53.F.11.11
FUNCTION
F 31 = Closed centres
32 = Open centres
33 = Pressured centres



Weight gr. 4200
Minimum piloting pressure 3 bar



Operational characteristic						
Fluid	Max working pressure (bar)	Temperature °C	Flow rate at 6 bar with $\Delta p=1$ (l/min)	Orifice size (mm)	Working ports size	Pilot ports size
Filtered and lubricated air	10 bar	-5 - +70	6500 l/min	mm 20	G 1"	G 1/8"

