

































# Electric and electronic connectors

## 1 CONNECTORS FOR ON/OFF VALVES

CODE AND DIMENSIONS	APPLICATION	INTERNAL VIEW PINOUT (1)	FRONT VIEW	CABLE GLAND Ø CABLE	REFERENCE RULES
<b>345</b> 	Female plastic connector - 4 pin: - position transducer for ZO(R)-T and ZO-L valves - inductive proximity, /FI option for DHI, DHE			PG7 ø 4 ÷ 6 mm	Protection degree IP 65 EN 60529
<b>664</b> <b>666</b> (black) <b>666/A</b> (grey) <b>667-24</b> <b>667-110</b> <b>667-220</b> 	Female plastic connector - 4 pin: - pressure switch type MAP - inductive proximity, /FI option for DKE-17*  Female plastic connector - 3 pin: - standard coil connector for ON/OFF - inductive proximity, /FI option for DKE-16*  Female plastic connector - 3 pin: - standard coil connector for ON/OFF with built-in led			PG11 ø 8 ÷ 10 mm	DIN 43650-A/ISO 4400 Protection degree IP 65 EN 60529
<b>ZBE-06</b> 	Female plastic connector - 4 pin: - position switch, /FV option			PG7 ø 2,5 ÷ 6,5 mm	M12 - coding A IEC 61076-2-101 Protection degree IP 67 EN 60529
<b>BKS-B-20-4-03</b> 	Female plastic connector - 4 pin (3 wire): - inductive proximity for LIFI Cable length: 3 m			Moulded on cable	M12 - coding A IEC 61076-2-101 Protection degree IP 67 EN 60529
<b>669 (2)</b> 	Female plastic connector - 3 pin: - optional electronic connector for ON/OFF valves with built-in rectifier bridge for supplying DC coils by AC current			PG11 ø 8 ÷ 10 mm	DIN 43650-A/ISO 4400 Protection degree IP 65 EN 60529
<b>E-SD/AC</b> 	Female plastic connector - 3 pin: - electronic connector which eliminate electric disturbances when AC solenoid valves are deenergized Power supply: 110/50, 115/60, 220/50, 230/60 V <sub>AC</sub>			PG11 ø 8 ÷ 10 mm	DIN 43650 Protection degree IP 65 EN 60529
<b>E-SD/DC</b> 	Female plastic connector - 3 pin: - electronic connector which eliminate electric disturbances when DC solenoid valves are deenergized Power supply: 12, 24, 48 V <sub>DC</sub>			PG11 ø 8 ÷ 10 mm	DIN 43650 Protection degree IP 65 EN 60529

(1) the wiring of electrical terminals has to be realized according to specific valve's technical table

## 2 CONNECTORS FOR PROPORTIONAL VALVES

CODE AND DIMENSIONS	APPLICATION	INTERNAL VIEW PINOUT (1)	FRONT VIEW	CABLE GLAND Ø CABLE	REFERENCE RULES
<b>666</b> (black) 	Female plastic connector - 4 pin: - standard coil connector for proportionals			PG11 ø 8 ÷ 10 mm	DIN 43650-A/ISO 4400 Protection degree IP 65 EN 60529
<b>ZM-7P</b> 	Female metallic connector - 7 pin: - main connector for integral electronic driver			PG11 ø 7 ÷ 9 mm	According to MIL-C-5015 Protection degree IP 67 EN 60529
<b>ZM-12P</b> 	Female metallic connector - 12 pin: - main connector for integral electronic driver			PG13,5 ø 8 ÷ 11 mm	DIN 43651 Protection degree IP 67 EN 60529
<b>ZM-5PF</b> 	Female metallic connector - 5 pin: - CANbus for integral electronic driver			Pressure nut ø 6 ÷ 8 mm	M12 - coding A IEC 60947-5-2 Protection degree IP 67 EN 60529

<b>ZM-5PM</b>		Male metallic connector - 5 pin: - CANbus for integral electronic driver			Pressure nut ø 6 ÷ 8 mm	M12 - coding A IEC 61076-2-101 Protection degree IP 67 EN 60529
<b>ZM-5PF/BP</b>		Female metallic connector - 5 pin: - PROFIBUS DP for integral electronic driver			Pressure nut ø 6 ÷ 8 mm	M12 - coding B IEC 61076-2-101 Protection degree IP 67 EN 60529
<b>ZM-5PM/BP</b>		Male metallic connector - 5 pin: - PROFIBUS DP for integral electronic driver			Pressure nut ø 6 ÷ 8 mm	M12 - coding B IEC 61076-2-101 Protection degree IP 67 EN 60529
<b>ZM-4PM/E</b>		Male metallic connector - 4 pin: - EtherCAT, POWERLINK, EtherNet/IP for integral electronic driver			Pressure nut ø 6 ÷ 8 mm	M12 - coding D IEC 61076-2-101 Protection degree IP 67 EN 60529
<b>ZH-5PM/1.5</b> <b>ZH-5PM/5</b>		Male plastic connector - 5 pin - single pressure/force transducer - analog position transducer Cable length: 1.5 m or 5 m			Moulded on cable	M12 - coding A IEC 61076-2-101 Protection degree IP 67 EN 60529
<b>ZH-5PM-2.2</b>		Male plastic connector - 4 pin: - double pressure/force transducers Splitting cable length: 2 m			Moulded on cable	M12 - coding A IEC 61076-2-101 Protection degree IP 67 EN 60529
<b>ZH-8PM/5</b> <b>ZH-8PM/10</b>		Male plastic connector - 8 pin: - digital position transducer Cable length: 5 m or 10 m			Moulded on cable	M12 - coding A IEC 61076-2-101 Protection degree IP 67 EN 60529
<b>ZBE-06</b>		Female plastic connector - 4 pin: - position transducer (LIQZO-T* size 50) - integral pressure transducer (TERS ) - position switch for safety valves, /FV option			PG7 ø 2,5 ÷ 6,5 mm	M12 - coding A IEC 61076-2-101 Protection degree IP 67 EN 60529
<b>ZBE-08</b>		Female plastic connector - 5 pin: - position transducer E-THT-15 (LIQZP)			PG7 ø 2,5 ÷ 6,5 mm	M12 - coding A IEC 61076-2-101 Protection degree IP 67 EN 60529
<b>ZH-7P</b>		Female plastic reinforced with fiber glass connector - 7 pin: - main connector for integral electronic driver			PG11 ø 8 ÷ 10 mm	According to MIL-C-5015 Protection degree IP 67 EN 60529
<b>ZH-12P</b>		Female plastic reinforced with fiber glass connector - 12 pin: - main connector for integral electronic driver			PG16 ø 6 mm x 2 cable	DIN 43651 Protection degree IP 67 EN 60529
<b>ZH-5P</b>		Female plastic connector - 5 pin: - RS232 Serial, CANbus - digital electronic driver E-MI-AS-IR, /M12 option			PG9 ø 6 ÷ 8 mm	M12 - coding A IEC 61076-2-101 Protection degree IP 67 EN 60529
<b>ZH-5P/BP</b>		Male plastic connector - 5 pin: - PROFIBUS DP			PG9 ø 6 ÷ 8 mm	M12 - coding B IEC 61076-2-101 Protection degree IP 67 EN 60529
<b>ZH-5PM</b>		Male plastic connector - 5 pin: - pressure, force, position transducers (TEZ/LEZ series 10 or lower)			PG7 ø 4 ÷ 6 mm	M12 - coding A IEC 61076-2-101 Protection degree IP 67 EN 60529











































(1) the wiring of electrical terminals has to be realized according to specific valve's technical table

### 3 CONNECTOR FOR PRESSURE TRANSDUCERS AND PRESSURE SWITCHES

CODE AND DIMENSIONS	APPLICATION	INTERNAL VIEW PINOUT (1)	FRONT VIEW	CABLE GLAND Ø CABLE	REFERENCE RULES
<b>ZBE-08</b>	Female plastic connector - 5 pin: - pressure transducer E-ATR8 - electronic pressure switch type E-DAP-2			PG7 ø 2,5 ÷ 6,5 mm	M12 - coding A IEC 61076-2-101 Protection degree IP 67 EN 60529

(1) the wiring of electrical terminals has to be realized according to specific valve's technical table

4 CONNECTORS FOR CK\* SERVOCYLINDERS

CODE AND DIMENSIONS	APPLICATION	INTERNAL VIEW PINOUT (1)	FRONT VIEW	CABLE GLAND Ø CABLE	REFERENCE RULES
<b>CON031</b> 	Straight female metallic connector - 5 pin: - magnetosonic transducer for CKF servocylinders - electronic conditioning card for CKN servocylinders Transducer output signal: analog			PG9 Ø 6 ÷ 8 mm	M12 IEC 61076-2-101 Protection degree IP 67 EN 60529
<b>CON041</b> 	Female plastic connector at 90° - 5 pin: - magnetosonic transducer for CKF servocylinders - electronic conditioning card for CKN servocylinders Transducer output signal: analog			PG9 Ø 6 ÷ 8 mm	M12 IEC 61076-2-101 Protection degree IP 67 EN 60529
<b>STCO9131-D06-PG7</b> 	Straight female metallic connector - 6 pin: - magnetosonic transducer for CKM servocylinders - magnetostrictive transducer for CKN servocylinders Transducer output signal: analog			PG7 Ø 4 ÷ 6 mm	Protection degree IP 67 EN 60529
<b>STCO9131-6-PG7</b> 	Female metallic connector at 90° - 6 pin: - magnetosonic transducer for CKM servocylinders - magnetostrictive transducer for CKN servocylinders Transducer output signal: analog			PG7 Ø 4 ÷ 6 mm	Protection degree IP 67 EN 60529
<b>STCO9131-D06-PG9</b> 	Straight female metallic connector - 6 pin: - CANopen input and output fieldbus interface for CKM servocylinders			PG9 Ø 6 ÷ 8 mm	Protection degree IP 67 EN 60529
<b>STCO9131-6-PG9</b> 	Female metallic connector at 90° - 6 pin: - CANopen input and output fieldbus interface for CKM servocylinders			PG9 Ø 6 ÷ 8 mm	Protection degree IP 67 EN 60529
<b>STCO9131-D07-PG9</b> 	Straight female metallic connector - 7 pin: - potentiometer transducer for CKM servocylinders Transducer output signal: digital SSI			PG9 Ø 6 ÷ 8 mm	Protection degree IP 67 EN 60529
<b>STCO9131-7-PG9</b> 	Female metallic connector at 90° - 7 pin: - potentiometer transducer for CKM servocylinders Transducer output signal: digital SSI			PG9 Ø 6 ÷ 8 mm	Protection degree IP 67 EN 60529
<b>560884</b> 	Straight male metallic connector - 5 pin: - PROFIBUS DP for CKM servocylinders (input)			PG9 Ø 6,5 ÷ 8,5 mm	M12 - coding B IEC 61076-2-101 Protection degree IP 67 EN 60529
<b>560885</b> 	Straight female metallic connector - 5 pin: - PROFIBUS DP for CKM servocylinders (output)			PG9 Ø 6,5 ÷ 8,5 mm	M12 - coding B IEC 61076-2-101 Protection degree IP 67 EN 60529
<b>560886</b> 	Female plastic connector at 90° - 4 pin: - PROFIBUS DP for CKM servocylinders (power supply)			PG7 Ø 3,5 ÷ 5 mm	M8 IEC 61076-2-104 Protection degree IP 67 EN 60529
<b>560888</b> 	Straight female plastic connector - 4 pin: - PROFIBUS DP for CKM servocylinders (terminator)			PG9 Ø 6,5 ÷ 8,5 mm	M12 - coding B IEC 61076-2-101 Protection degree IP 67 EN 60529
<b>STCO9131-D04-PG7</b> 	Straight female metallic connector - 4 pin: - potentiometer transducer for CKP servocylinders - inductive transducer for CKV servocylinders Transducer output signal: analog			PG7 Ø 4 ÷ 6 mm	M12 - coding A IEC 61076-2-101 Protection degree IP 67 EN 60529
<b>STCO9131-4-PG7</b> 	Female plastic connector at 90° - 4 pin: - potentiometer transducer for CKP servocylinders - inductive transducer for CKV servocylinders Transducer output signal: analog			PG7 Ø 4 ÷ 6 mm	M12 - coding A IEC 61076-2-101 Protection degree IP 67 EN 60529

(1) the wiring of electrical terminals has to be realized according to specific valve's technical table