



10
kN

5
kN

350
nm

12
kg

10
l/min


45 \varnothing 25
mm


1/4"
BSP


250
bar


1/4"
BSP


200
bar


300
bar

Rotator's upper mount is applied in EYE form factor of the knuckle joint. Robust and tough built to withstand even overloads. The wide of eye is common standard width 45mm and the knuckle pin diameter 25mm.

Hydraulic rotator FHR 1.000L is cost-effective solution generally for seasonal use in forestry, agriculture, road and building construction, general cargo and material handling.






FHL 01-A/B-
45/25

Rotator lower mount is applied in AXLE form factor to mount in grapple / tool mounting tube or adaptor and by fixing with pin. Axle (shaft) diameter is 39.5mm and the fixing pin (not included) diameter 20mm


39.5 \varnothing 20
mm


1/4"
BSP



For additional information relating to price levels and technical data, please contact sales@formiko.lv

Formiko Hydraulic s Ltd

Dzirciema Str. 119 k-1,
Riga LV1055 LATVIA

+371 294 49 552

+371 264 59 383

sales@formiko.lv

www.formiko.lv

On request by special conditions there are metric nipples available for rotator FHR 1.000L



FORESTRY

AGRICULTURE

CONSTRUCTION





Hydraulic rotator FHR 1.000L is cost-effective solution generally for seasonal use in forestry, agriculture, road and building construction, general cargo and material handling.



Rotator's upper mount is applied in EYE form factor of the knuckle joint. Robust and tough built to withstand even overloads. The wide of eye is common standard width 45mm and the knuckle pin diameter 25mm.



Rotator lower mount is applied in AXLE form factor to mount in grapple / tool mounting tube or adaptor and by fixing with pin. Axle (shaft) diameter is 39.5mm and the fixing pin (not included) diameter 20mm



Rotator FHR 1.000L based on reliable vane type hydraulic motor which delivers torque up to 350Nm at 25MPa.



Formiko rotator FHR 1.000L is compatible with FHL 01-A/B-45/25 series links.



Rotator for shipping is packed in compact solid cardboard box with dimensions 280x180x180mm.



Formiko Hydraulics FHR 1.000L is the smallest rotator commonly used with the forestry ATV trailer or paving equipment in the road construction



We providing TWO year warranty for this rotator.

For additional information relating to price levels and technical data, please contact sales@formiko.lv

Formiko Hydraulic s Ltd

Dzirčiema Str. 119 k-1,
Rīga LV1055 LATVIA

+371 294 49 552
+371 264 59 383
sales@formiko.lv
www.formiko.lv

On request by special conditions there are metric nipples available for rotator FHR 1.000L



FORESTRY



AGRICULTURE



CONSTRUCTION

