




ROTATORI FHR 3.000L









For additional information relating to price levels and technical data, please contact sales@formiko.lv





Hydraulic rotator FHR 3.000L is cost-effective solution generally for seasonal use in forestry, agriculture, general cargo and material handling.



Rotator's upper mount is applied in EYE form factor of the knuckle joint. Robust and tough built to withstand even overloads. The wide of eye is common standard width 60mm and the knuckle pin diameter 25mm.



Rotator lower mount is applied in AXLE form factor to mount in grapple / tool mounting tube or addaptor and by fixing with pin. Axle (shaft) diameter is 49.5mm and the fixing pin (not included) diameter 30mm



 $Rotator \ {\rm FHR} \ {\rm 3.000L} \ {\rm based} \ {\rm on \ reliable} \ {\rm vane \ type \ hydraulic \ motor \ which \ delivers \ torque \ up \ to \ {\rm 900Nm} \ at \ {\rm 25MPa}.$



Formoko rotator FHR 3.000L is compatible with FHL 01-A/B-60/25 and FHL 01B-A/B-60/25 series links.



Rotator for shipping is packed in compact solid cardboard box with dimensions 340x230x240mm.



We providing TWO year warranty for this rotator.

For additional information relating to price levels and technical data, please contact sales@formiko.lv

