




RPC1-*/4M


FLOW CONTROL VALVE

SERIES 10


MODULAR VERSION ISO 4401-05

p max **250** bar
Q max (see table of performances)

MOUNTING INTERFACE



OPERATING PRINCIPLE




CONFIGURATIONS (see hydraulic symbols table and identification code - par. 1)

PERFORMANCES (measured with mineral oil of viscosity 36 cSt at 50°C)

Maximum operating pressure	bar	250
Maximum flow rate in controlled lines	l/min	1-4-10-16-22-30
Maximum flow rate in the free lines		100
Reverse free flow maximum flow rate		40
Ambient temperature range	°C	-20 / +60
Fluid temperature range	°C	-20 / +80
Fluid viscosity range	cSt	10 ÷ 400
Fluid contamination degree	According to ISO 4406:1999 class 20/18/15	
Recommended viscosity	cSt	25
Mass: RPC1-*/4M/ A-B RPC1-*/4M/ D only modular block ISO 4401-05 without flow control valves: RPC1-K/4M/D	kg	4,3 5,6 3

HYDRAULIC SYMBOLS



NOTE: Please see catalogue 32 200 for detailed information about the RPC1 flow control valve.



RPC1*/4M

SERIES 10

1 - IDENTIFICATION CODE

R	P	C	1	-		/	4	M	/		/	10	/	
----------	----------	----------	----------	----------	--	----------	----------	----------	----------	--	----------	-----------	----------	--

Pressure and temperature compensated flow control valve

Flow adjustment range: _____

1 = 1 l/min	16 = 16 l/min
4 = 4 l/min	22 = 22 l/min
10 = 10 l/min	30 = 30 l/min

K = only for ISO 4401-05
modular block supplied without flow control valves

Modular version _____
ISO 4401-05 size

Seals: omit for mineral oils
V = viton for special fluids

Series No. (the overall and mounting dimensions remain unchanged from 10 to 19)

A = control from chamber A of the actuator
B = control from chamber B of the actuator
D = control from chambers A and B of the actuator
(A and B configurations are not available in K version)

2 - HYDRAULIC FLUIDS

Use mineral oil-based hydraulic fluids HL or HM type, according to ISO 6743-4. For these fluids, use NBR seals. For fluids HFDR type (phosphate esters) use FPM seals (code V). For the use of other kinds of fluid such as HFA, HFB, HFC, please consult our technical department. Using fluids at temperatures higher than 80 °C causes a faster degradation of the fluid and of the seals characteristics.

The fluid must be preserved in its physical and chemical characteristics.

3 - OVERALL AND MOUNTING DIMENSIONS

