ORDER PICKER





CK-05 | Order picker, 500 kg

ORDER PICKING AT HIGH HEIGHTS

Silverstone CK-05 solves many of the high altitude problems and tasks that you may face when working in industry, warehouse and retail shops. Order picking up to 6,3 m is no problem.

CK-O5 is simple and easy to maneuver thanks to the electric steering and well-designed controls. CK-O5 only needs 1,8 meter wide aisle to make a U-turn.

Maintenance work on high levels often means bulky and wobbly ladders in action and yet stability and space is limited. With Silverstone CK-05 you drive around smoothly and easily with space for both materials and tools on board. Do you need to move around the properties while towing one or many carts? No problem, CK-05 solves this task with elegance and safety. CK-05 is equipped with non-marking polyurethane wheels.

PERFECT FOR

- WORKSHOPS
- STORES
- WAREHOUSES





Front load tray



Art.no		CK-05-4880
Arr.no		CK-05-4880
Туре		Rider stand
Capacity	(kg)	500
Maximal height working platform	(mm)	4880
Outer dimensions (LxWxH)	(mm)	1610x860x2120
Ground clearance	(mm)	50
Weight	(kg)	1530
Wheel type		PU/Rubber
Area front load tray	(mm)	520x800
Height working platform, rear	(mm)	346x660
Maximal working height	(mm)	6300
Operators compartment size	(mm)	545x800
Wheel base	(mm)	1256
Turning radius (Wa)	(mm)	1450
Travel speed	(km/h)	5,5
Lift speed, load/no load	(cm/s)	17 - 21
Lowering speed, load/no load	(cm/s)	35 - 26
Battery	(V/Ah)	24/280
Battery type		Electromagnetic
Brakes		Maintenance fre
Drive motor	(kW)	AC 1,7
Lift motor	(kW)	2,2
Steering system		ZAPI

JXO | Order picker, 350 kg

With a working height of up to 5 m, the JXO is an alternative to ladders that are used today in stores, maintenance work or when picking. Only 750mm wide, the JXO is suitable for driving in narrow spaces and corridors. The load surface can be raised and lowered (electrically), which gives a good visibility while driving as well as an ergonomic working position.

- COMPACT DESIGN
- WORKING HEIGHT UP TO 5 METERS
- LOADING AREA WITH ELECTRIC LIFTING AND LOWERING
- DRIVING SPEED: 5KM/H (PLATFORM DOWN)
- BUILT-IN CHARGER 230V
- BLUESPOT FOR INCREASED SAFETY



Art.no		JXO
Туре		Rider stand
Capacity	(kg)	350
Maximal height working platform	(mm)	3000
Outer dimensions (LxWxH)	(mm)	1440x750x1370
Ground clearance	(mm)	35
Weight	(kg)	800
Wheel type		PU/Rubber
Area front load tray	(mm)	540x740
Maximal working height	(mm)	ca 5000
Wheel base	(mm)	1095
Turning radius	(mm)	1260
Travel speed, load/no load	(km/h)	6/6,5 km/h
Lowering speed, load/no load	(cm/s)	30 - 29
Battery	(V/Ah)	24/120
Battery type		Maintenance fre
Brakes		Electromagnetic
Drive motor	(kW)	DC 0,65
Lift motor	(kW)	2,2
Steering system		ZAPI

