

TRANSPARENT POLYURETHANE SH98 TUBES

Code	∅		Thickness	Pressure at 23°C		Radius min. Bend	Weight	Available colours						Length	
	External	Internal		Working	Bursting			Natural	Blue	Black	Red	Yellow	Green		Orange
	mm.	mm.	mm.	bar	bar	mm.	g/m	T	B	N	R	G	V	A	m
PUX42*	4,00	2,00	1,00	19	56	11	11,5	x	x		x				100
PUX425*	4,00	2,50	0,75	13	40	15	9,3	x	x		x				100
PUX53*	5,00	3,00	1,00	15	46	14	15,3	x	x		x				100
PUX64*	6,00	4,00	1,00	13	40	18	19,2	x	x		x				100
PUX85*	8,00	5,00	1,50	17	52	25	37,4	x	x		x				100
PUX855*	8,00	5,50	1,25	12	36	30	32,3	x	x		x				100
PUX86*	8,00	6,00	1,00	9	28	35	26,8	x	x		x				100
PUX1065*	10,00	6,50	1,75	13	40	30	55,3	x	x		x				100
PUX107*	10,00	7,00	1,50	11	34	30	48,8	x	x		x				100
PUX1075*	10,00	7,50	1,25	9	26	40	41,9	x	x		x				100
PUX108*	10,00	8,00	1,00	7	22	45	34,5	x	x		x				100
PUX128*	12,00	8,00	2,00	9	28	50	76,6	x	x		x				100
PUX129*	12,00	9,00	1,50	8	24	50	60,3	x	x		x				100

NB: In the code there is an *, this must be replaced with the colour code of the tube.

EXAMPLE: Tube 8x6 PUX Blue - Code PUX86B.

Working temperature: from -20°C to +60°C.

Pressure correction scale according to temperature

0°C	23°C	30°C	40°C	50°C	60°C
1	1	0,84	0,70	0,60	0,52