



1

<b>Pneumatic-Spring</b>	2/2 3/2	Ordering code <b>104.1.11.1.C.F</b>	2/2 3/2	<b>Pneumatic-Spring</b>			
Lateral connections		TYPE T 22 = 2 ways 32 = 3 ways CONNECTION TYPE C L = Lateral P = Rear FUNCTION A = Normally Open (N.O.) C = Normally Closed (N.C.)		Rear connections			
  Weight gr. 25 Minimum piloting pressure 2,5 bar		  Weight gr. 25 Minimum piloting pressure 2,5 bar					
<b>Operational characteristics</b>	Fluid Filtered air, with or without lubri-	Max working pressure 10 bar	Operating Temperature Min. -5°C Max. +50°C	Flow rate at 6 bar with Δp=1 90 NI/min	Orifice size mm 2,5	Working port size ø4 tube	Pilot port size M5

<b>Pneumatic-Spring</b>	3/2	Ordering code <b>105.1.11.1</b>	5/2	<b>Pneumatic-Spring</b>			
Lateral connections		TYPE T 32 = 3 ways 52 = 5 ways		Rear connections			
  Weight gr. 90 Minimum piloting pressure 2,5 bar		  Weight gr. 100 Minimum piloting pressure 2,5 bar					
<b>Operational characteristics</b>	Fluid Filtered air, with or without lubri-	Max working pressure 10 bar	Operating Temperature Min. -5°C Max. +70°C	Flow rate at 6 bar with Δp=1 120 NI/min	Orifice size mm 2,5	Working port size M5	Pilot port size M5

<b>Pneumatic-Differential external</b>	3/2	Ordering code <b>105.1.11.2</b>	5/2	<b>Pneumatic-Differential external</b>			
Lateral connections		TYPE T 32 = 3 ways 52 = 5 ways		Rear connections			
  Weight gr. 110 Minimum piloting pressure 2,5 bar		  Weight gr. 120 Minimum piloting pressure 2,5 bar					
<b>Operational characteristics</b>	Fluid Filtered air, with or without lubri-	Max working pressure 10 bar	Operating Temperature Min. -5°C Max. +70°C	Flow rate at 6 bar with Δp=1 120 NI/min	Orifice size mm 2,5	Working port size M5	Pilot port size M5