

## Tepalas Acmos WAXILIT

### Information



## WAXILIT® 22 - 71 F lubricant

For woodworking machines

---

### BASIS:

No substances regarded as toxic or carcinogenic according to the Regulations concerning Dangerous Substances are used in the production of **WAXILIT 22-71 F**.

### PROPERTIES:

**WAXILIT 22-71 F** is a silicon-free lubricant for woodworking machines with an automatic feeder. **WAXILIT 22-71 F** ensures a good lubrication effect. No blockage of pumps, pipes and nozzles.

### APPLICATION:

Pour **WAXILIT 22-71 F** into the storage tank of the lubricant pump. The lubricant can also be used with a hand spray-gun (preferably metall).

Meter the lubricant quantity according to the type of wood →  
Soft wood: less lubricant  
Hard wood: more lubricant

**WAXILIT 22-71 F** does not leave spots. There have been no reports of trouble during subsequent staining, varnishing or gluing.

Ask **WAXILIT 22-60** for use with wet wood, new wood and coarse wood.

### SUPPLY FORM:

Non-returnable drums with a net capacity of 5 kg, 20 kg and 150 kg.  
Boxes of 12 x 1 kg.  
Storage time 18 months.

Additional information can be found in the EU safety data sheet.

Our technical service department will gladly advise you on all questions concerning the application of our products. Free samples can be made available to you on request.

All information given is accurate to the best of our knowledge but provided without guarantee.

Bremen, 24 January 2011