

## SL 500



UPDATED: 12.07.11



A fast acting, penetrating grease for lubrication of general moving components.

**Part N°:**

84339 (KSL) - 500ml aerosol

83688 (KSL -85) 85ml aerosol

### Features & Benefits

- Excellent Penetrant - Gets to where lubricant is required
- Clear formulation - Invisible protection
- Moisture repellent - Protects against corrosion
- High adhesion - Stays where it is needed
- High Lubricity - Reduces wear and friction

### Applications

SL 500 is a lubricant based on mineral oils, poly-isobutene, anti-wear, anti-corrosion additives and PTFE.

SL 500 is a clear spray grease with excellent penetrating ability and very high adhesion, once the propellant has flashed off, it leaves a high degree of both protection and lubricating properties.

SL 500 is designed for lubricating general moving components during the service schedule, such as:-

- Door Hinges
- Check Straps
- Door Locks
- Bonnet and Boot hinges and catches
- Pedal pivots
- Fuel cap locks
- Control linkages / cables / chains

### Instructions

Spray directly on to moving parts of the component requiring lubricating.

### Hints & Tips

DS118



**SL 500****KENT** **Technical Information**

|              |   |  |           |
|--------------|---|--|-----------|
| Appearance:  | Clear Gel like liquid   | Timken OK load, ASTM D 2782 :                                  | > 50      |
| Odour:       | Negligible  | 4-ball welding DIN 51350                                       |           |
| Packaging:   | 500ml aerosol – label codes<br>11-45-21<br>85ml aerosol - label code 11 | Part 2: EP: 1500 rpm, OK load: 2200N, welding load: 2300N      |           |
| VOC:         | 410 g/l   | Part 3: Anti-wear: scar diameter / 1500rpm / 1 h / 200N: 0, 30 |           |
| Tariff Code: | 3403 19 19  | Water separation / demulsifying: ASTM D 1401: 40-40-0          |           |
| Shelf Life:  | 30 months   | Copper corrosion: ASTM D 1300 3h / 100°C: 1-b                  |           |
| SDS:         | yes   | Application temp:  | 15-25°C   |
|              |   | Specific gravity:  | 0.687g/ml |
|              |   | Corrosion ASTM D 665:  |           |
|              |   | Part A: distilled water: No corrosion                          |           |
|              |   | Part B: Sea water: No corrosion                                |           |

**Associated Products:** Spray Rusty Penetrant, Rusty Clear, HT Oil, Acrysol, Speedy 500**Market Segments****Primary****Secondary****Health & Safety Information****Dangerous for the environment****EXTREMELY FLAMMABLE**

R12 Extremely Flammable  
R51/53 Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.  
R66 Repeated exposure may cause skin dryness or cracking.  
R67 Vapours may cause drowsiness and dizziness.  
S23 Do not breathe spray.  
S46 If swallowed, seek medical advice immediately and show this container or label.  
S51 Use only in well-ventilated areas.  
WARNING: Pressurised container: protect from sunlight and do not expose to temperatures exceeding 50°C. Do not pierce or burn, even after use. Do not spray on a naked flame or any incandescent material.

In order to provide you with the most appropriate Personal Protective Equipment when using our products, KENT advises that you follow the guidelines on the packaging of the product before use. The guidelines are there for your protection and KENT provides a range of Personal Protection Equipment such as clothing, eye glasses, goggles, face shields and breathing apparatus, complying with the latest European legislation. If you require further advice then please phone our freephone number and we will be pleased to help you. Telephone: 0800 136925

**Terms and Conditions**

No part of this publication may be reproduced, transmitted or stored, electronically, mechanically or photocopied without the prior permission of KENT UK.  
This data sheet and its contents (the "Information") belong to KENT UK or are licensed to it. No licence is granted for the use of it other than for information purposes in connection with the products to which it relates. No licence of any intellectual property rights is granted.

The Information is subject to change without notice and replaces all data sheets previously supplied. The Information supplied is believed to be accurate but the business assumes no responsibility for its accuracy or completeness, any error from or omission in it nor for any use made of it. Users of this data sheet should check for themselves the Information and the suitability of the products for their purpose and not make any assumptions based on information included or omitted. Liability for loss or damage resulting from any reliance on the Information or use of it (including

liability resulting from negligence or where the business was aware of the possibility of such loss or damage arising) is excluded. This will not operate to limit or restrict the business liability for death or personal injury resulting from its negligence.

**Registered Office:** 151 Longsight, Bolton, Lancashire BL2 3JE  
Registered in England N°: 02519917  
VAT Registration N°: 125 0226 61  
All rights reserved.

**KENT UK, Pitreavie Crescent, Pitreavie Business Park, Dunfermline, Fife KY11 8UQ**  
**Tel :** Freephone 0800 136925 or 01383 737393 between 08:30-17:30 Monday-Thursday, 09:00-15:00 on Fridays'. For out of hours queries please Fax us on 01383 735829 or  
**Email:** [KENTsales.UK@kenturope.com](mailto:KENTsales.UK@kenturope.com)

**DS118**