

## DC-series | Powered pallet truck, 1800/2000 kg

# POWERED PALLET TRUCK

A compact and fast electric pallet truck with electrical lifting and manual lowering function. Maintenance-free and removable 20Ah lithium battery provides minimum 3 hours effective use. Charger included and the charging time is only 2,5 hours.

- LITHIUM BATTERY
- EXTREMELY COMPACT DESIGN
- TURNING RADIUS 1345 MM
- CHARGER INCLUDED
- ERROR CODE DISPLAY
- BATTERY CHANGE IN 5 SEC



**LI-ION**  
LITHIUM TECHNOLOGY

TECHNICAL INFORMATION		
Art. no	DC18	DC20
Type	Walkie	Walkie
Capacity (kg)	1800	2000
Ground clearance (mm)	35	35
Fork dimensions (LxWxH) (mm)	1150x150x50	1150x150x50
Outer fork width (mm)	550	550
Weight (kg)	148	150
Wheel type	PU/PU	PU/PU
Steering wheel (mm)	Ø210x70	Ø210x70
Fork wheel (mm)	Ø80x60	Ø80x60
Wheels	1x /4	1x /4
Load center (mm)	600	600
Total length (mm)	1550	1550
Total width (mm)	550	550
Lifting height (mm)	200	200
Turning radius (mm)	1345	1345
Travel speed, load/no load (km/h)	4,2-4,5	4,2-4,5
Length with 1000x1200 pallet (mm)	1750	1750
Length with 800x1200 pallet (mm)	1800	1800
Max gradeability load/ no load (%)	5/10	5/10
Battery (V/Ah)	48/20	48/20
Battery type	Litium maint. free	Litium maint. free
Brakes	Electromagnetic	Electromagnetic
Control system	CURTIS	CURTIS
Drive motor (kW)	DC 0,75	DC 0,75
Lift motor (kW)	0,8	0,8
Price		
* Polyurethane wheel = PU		

# POWERED PALLET TRUCK

## ESL15L | Powered pallet truck, 1500 kg

Smooth and easy-to-use powered hand pallet truck. Maintenance-free and removable 24V/30Ah battery provides 3 hours of effective use. External charger.

- **COMPACT DESIGN**
- **MAINTENANCE-FREE BATTERIES**
- **PIN CODE LOCK**
- **CURTIS CONTROLLER**
- **AVAILABLE WITH DIFFERENT FORK LENGTHS**

900MM, 1500MM AND 1800MM



**LI-ION**  
LITHIUM TECHNOLOGY

TECHNICAL INFORMATION	
Art. no	ESL15L
Type	Walkie
Capacity (kg)	1500
Lifting height (mm)	85-200
Outer dimensions (LxWxH) (mm)	1603x545x1170
Ground Clearance (mm)	30
Fork dimensions (LxWxH) (mm)	1150x150x50
Outer fork width (mm)	540
Weight (kg)	142
Wheel type	PU/PU
Steering wheel (mm)	Ø210x70
Fork wheel (mm)	2x Ø80x60
Wheels (x=drive wheel)	1x/4
Load center (mm)	600
Length with 1000x1200 pallet (mm)	1804
Length with 800x1200 pallet (mm)	1854
Turning radius (mm)	1398
Travelspeed load - no load (km/h)	4,2-4,5
Battery (V/Ah)	24/20
Battery type	Litium maint.free
Brakes	Electromagnetic
Drive motor (kw)	DC 0,75
Lift motor (kw)	0,8
Control system	CURTIS
Pris	



**T20-15F4 | Powered pallet truck, 1500 kg**

Maintenance free lithium battery. Slots for 2 lithium batteries, 1 is included. Compact design.

- **MAINTENANCE FREE BATTERY**
- **COMPACT DESIGN**
- **SPACE FOR 2 LITHIUM BATTERIES - (1 BATTERY INCLUDED)**
- **1500 KG LOAD CAPACITY**
- **EXTERNAL CHARGER**



TECHNICAL INFORMATION		
Art. no		T20-15F4
Type		Walkie
Capacity	(kg)	1500
Lifting height	(mm)	105
Outer dimensions (LxWxH)	(mm)	1550x590x1190
Ground Clearance	(mm)	25
Fork dimensions (LxWxH)	(mm)	1150x150x55
Outer fork width	(mm)	560
Weight	(kg)	120
Wheel type		PU
Steering wheel	(mm)	Ø210x70
Fork wheel	(mm)	2x Ø80x60
Wheels (x=drive wheel)		1x/4
Load center	(mm)	600
Length with 1000x1200 pallet	(mm)	2160
Length with 800x1200 pallet	(mm)	2025
Turning radius	(mm)	1360
Travelspeed load - no load	(km/h)	4,0-4,5
Battery	(V/Ah)	24/20
Battery type		Litium maint.free
Brakes		Electromagnetic
Drive motor	(kw)	DC 0,75
Lift motor	(kw)	0,5
Pris		
* Polyurethane wheel = PU		