TECHNICAL DATA





ROTTNE F15^D



ENGINE

Type JD 6068 HFC 08 Power Tech PVS, Final Tier 4 (FT4)

Output 164 kW / 220 hp at 1800 rpm Torque 963 Nm (710 lb ft) at 1500 rpm

Cylinder volume
6.8 liter (415 in³)
Diesel tank
165 litres (44 US gal)

TRANSMISSION

Type D5 controlled hydrostatic/mechanical with full

capacity control. 3 gear steps.

Tractive force 177 kN (39 800 lbf)
Speed, gear 1 0 - 5 km/h (0 - 3.1 mph)
Speed, gear 2 0 - 9.5 km/h (0 - 5.9 mph)
Speed, gear 3 0 - 25 km/h 0 - 15.5 mph)

BRAKES

Type 2-circuit electrically/hydraulically operated negative

wet disc brakes. Automatic load brake. Spring-assisted

parking and emergency brake.

WHEEL EQUIPMENT

8 WD 710/45 x 26.5

CHASSIS

Type Central joint with slew bearing and mid lock. Bolted

welded load bunks. Front headboard and first bunk

hydraulically movable. ng angle +/- 43°

Steering angle +/- 43° Max. steering touque 74.9 kNm (55 240 lb ft)

Horizontalangle +/- 20°

HYDRAULIC SYSTEM

Type Load-sensing system, entirely separated from the

transmission.

Pump capacity 210 litres (55 US gal) / 1500 rpm Working pressure 3 - 22 MPa (435 - 3 200 psi)

Degree of filtration 10 micron

Tank volume 105 litres (28 US gal)

ELECTRICAL SYSTEM

Type

Battery Alternator Machine control system Working lights

CAB

Type

Noise level Climate system

CRANE

Type

Lifting torque Angle of rotation

Service weight from

Reach

Torque

WEIGHT AND DIMENSIONS

Width
Length
Transportation height
Ground clearance (at articulated frame lock)
Loading capacity

Loading capacit

24 volt electrical system with CAN-bus technology. 2 x 142 Ah 150 A ROTTNE D5, with 9 20 pcs


Spacious, vibration-proof safety cab. ISO certified 67 dBA ACC

Jib arm crane RK125 with dual slew cylinders and telescope 1.4 m / 2.4 m / double telescope. 125 kNm (92 200 lb ft)


7.2 / 8.4 / 10 m (23.5 / 27.5 / 33 ft) 35.8 kNm (26 400 lb ft)

18 700 kg (41 225 lbs) 2 890 mm (114 in) 9 834 mm (387 in) 3 819 mm (150,5 in) 668 mm (26 in) 15 000 kg (33 100 lbs)


4.8 - 5.7 m² (52 - 61 ft²)











EQUIPMENT

Active Load Space ALS, Chains, Lighting Xenon or LED, Sprinklers, Engine/cab heater, Blinds, Mobile telephone, Vacuum pump, Reversing camera, GPS/Geoinfo, Filler pump, Green oil, Colour printer, Mobile broadband, Orbitrol steering, Full toolkit, Central lubrication, Tracks, Forwarder computer, Extended wagon frame, Extra load bunk, Load bunks "Wide load", Cab damping system COMFORT LINE, Dozer blade, Double telescope, Balanced bogie system, Bogie lift,

Contact your local dealer for more information. www.rottne.com

